MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0568 24" INDUSTRIAL BANDSAW 5 HP SINGLE-PHASE

Product Dimensions:

Weight	836 lbs.
Length/Width/Height	47-5/8 x 31-1/4 x 83-1/2 in.
Foot Print (Length/Width)	41-3/8 x 23-1/2 in.

Shipping Dimensions:

Type	Not Available
Content	Not Available
Weight	N/A
Length/Width/Height	N/A x N/A x N/A

Electrical:

Switch	Magnetic with Thermal Overload Protection
Switch Voltage	220V
Cord Gauge	8 gauge
Recommended Breaker Size	35 amp
Plug	No

Motors:

Main

Type	TEFC Capacitor Start Induction
Horsepower	5 HP
Voltage	220V
Prewired	220V
Phase	Single
Amps	30A
Speed	1725 RPM
Cycle	60 Hz
Number Of Speeds	1
Power Transfer	V-Belt
Bearings	Shielded and Permanently Lubricated

Main Specifications:

Operation

Blade Speeds	5300 FPM
Table Tilt	Right 45 deg.

Cutting Capacities

Height Capacity At Blade	16-1/4 in.
Overall Height Capacity	16-1/4 in.
Throat Capacity Left of Blade	24-1/2 in.

The information contained herein is deemed accurate as of 3/20/2008 and represents our most recent product specifications. Due to our ongoing improvement efforts, this information may not accurately describe items previously purchased.

Blade Information

Standard Blade Length	181 in.
Blade Length Range	180 - 181-1/2 in.
Blade Width Range	1/4 - 1-1/2 in.
Upper Blade Guides	Ball Bearing
Lower Blade Guides	Ball Bearing

Table Information

Table Length	23-5/8 in.
Table Width	33-1/2 in.
Table Thickness	2 in.
Floor to Table Height	34-1/2 in.

Fence Information

Locks in Front	Yes
Locks in Rear	No
Adjustable for Blade Lead	No

Construction

Table Construction	Precision Ground Cast Iron
Rip Fence	Precision Ground Cast Iron
Base Construction	Steel
Body Construction	Pre-Formed Steel
Upper Wheel	Computer Balanced Cast Iron
Lower Wheel	Computer Balanced Cast Iron
Tire Material	Rubber
Wheel Cover	Pre-Formed Steel
Paint	Powder Coated

Other Related Information

Wheel Diameter	24-3/4 in.
Wheel Width	1-3/4 in.
Number of Dust Ports	2
Dust Port Size	4 in.
Mobile Base	G7315, G8685

Other Specifications:

ISO Factory	ISO 9001
Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	ID Label
Assembly Time	30 minutes

Features:

Quick Change Blade Release/Tensioner
Blade Tension Indicator
Micro Adjusting Rack and Pinion Table Tilt
Height Scale Measurement
Foot Brake Stop
Included Miter Gauge
Rack and Pinion Upper Guide Adjustment
Magnifying Window Over Fence Scale
Hinged Wheel Covers with Safety Lock

The information contained herein is deemed accurate as of 3/20/2008 and represents our most recent product specifications. Due to our ongoing improvement efforts, this information may not accurately describe items previously purchased.